


USING WITH NOKIA 6650


ACTIVATING THE BLUETOOTH

You must activate the Bluetooth feature of your phone to be able to establish a Bluetooth connection between your phone and your SuperTooth II kit as well as with other Bluetooth devices.

1. Press **Menu > Connectivity > Bluetooth**.
2.  will be highlighted. Press **Select > Choose On**. ("Bluetooth switched on" will be displayed.)
3. Press **Back** or **Exit** as many times as needed to return to standby mode.

PAIRING TO THE CELLULAR PHONE (Not possible while charging the SuperTooth II)


Pairing will create a link or connection between the two Bluetooth devices - the SuperTooth II kit and your phone.

1. This SuperTooth II kit supports either **Handsfree** or **Headset** pairing mode. First, refer to **Compatibility Table** for suggested pairing modes to be able to determine what pairing mode is best for your phone. **Handsfree** and **Headset** profile differs in pairing procedure. (*Note: In the Compatibility Table, you can find that Nokia 6650 belongs to Handsfree Profile.*) Proceed with the instructions.
2. Bring the mobile phone at about 20cm from SuperTooth II.
3. The SuperTooth II is initially off. Turn it on by flipping up the **Swivel Arm(1)** to 55° position. The **Bluetooth Indicator(9)** will glow (*blue blink*).
4. Simultaneously press the **Reject Button(2)** and **Pick-Up/Hang-Up Button(7)** for about 10seconds. A distinctive tone will be heard and the Bluetooth Indicator LED will change from blinking blue to alternate blinking red and blue. SuperTooth II is now in **Handsfree Pairing Mode**.
5. While the kit is at pairing mode, access the Bluetooth menu of your phone. Press **Menu > Connectivity > Bluetooth**.
6.  is highlighted. Scroll down to **Search for audio enhancements > Select**. The phone will then search for pairable devices until it displays them in the list.
7. Choose the name of this kit (*SuperTooth II*) and press **Select**.
8. Enter **0000** as passcode then press **Ok**. ("Paired with SuperTooth II" and "Connected to SuperTooth II" will be briefly shown.)
9. Press **Back** or **Exit** as many times as needed to return to standby mode. Pairing has been successful if the alternating red/blue lights of **Bluetooth Indicator(9)** now has changed to plain blinking blue. (Normally, the phone would also show briefly on its display if it's already paired and connected to the SuperTooth or if pairing with it failed.)

The SuperTooth II kit is now ready to use.

AUTO ACCEPT MODE

When the SuperTooth is turned off, its link with the phone is disconnected. This auto accept mode procedure is recommended to allow automatic reconnections (*between SuperTooth II and your phone*) the moment the kit is turned back on.

1. Press **Menu > Connectivity > Bluetooth**.
2.  will be highlighted. Scroll down to **View Paired devices > Highlight the name of this kit (SuperTooth II)** then press **Options > Request Conn. Authorisation > Select No**. ("No authorisation required" appears briefly.)
3. Press **Back** or **Exit** as many times as needed to return to standby mode.

ANSWERING / ENDING A CALL

When you receive a call, ring tone will be heard simultaneously on SuperTooth II and on the phone or on the SuperTooth II only (*depending on your phone model*).

1. Just shortly press **Pick-Up/Hang-Up Button(7)** to answer the call.
2. When communication is over, press the **Pick-Up/Hang-Up Button(7)** to terminate the call.

MAKING A CALL

Normal dialing

Dial the number in your phone. Audio will be on the SuperTooth II.

Note: With some phones like Siemens S55; Panasonic X70, audio is always on the phone during an outgoing call. You will need to press Pick-Up/Hang-Up Button(7) to transfer the audio to your kit. (Also, refer to "Compatibility Table" for other helpful remarks.)

Voice dialing

Note: Voice dialing entries must be stored in the phone's memory (not on the SIM card!).

1. First, you have to record for a "voice command" or "voice tag" in your phone. Record your voice command in a quiet place so that only your voice will be recorded on the phone.
2. **Recording for voice dialing:** Press **Names** button > **Search**.
3. Choose a contact then press **Details > Options > Add Voice tag**.
4. Follow the instructions displayed. When recording is successful, the voice will be played back to you then "**Voice tag saved**" will be briefly shown.
5. Press **Back** or **Exit** as many times as needed to return to standby mode.

When recording is done, execute voice dialing in your kit by proceeding with the instructions.

6. Shortly press **Pick-Up/Hang-Up Button(7)**.
7. A beep will then be heard on the SuperTooth II prompting the user to say a voice name or voice tag of a person to call.
8. Say the name. The name will be played back to you (audio on kit). The phone will then place the call automatically.

REDIALING (Handsfree profile only)

Make a long press on the **Pick-Up/Hang-Up Button(7)**. Audio will be on the SuperTooth II.

AUDIO TRANSFER

Kit to Phone

Flip down the **Swivel Arm (1)** to 0° position (or turn-off the unit). This will automatically transfer the audio from the kit to the phone.

Phone to Kit

For Nokia Phones:

Flip up the **Swivel Arm** from 0° to 55° or 210° positions. (or turn-on the unit). This will automatically transfer the audio from phone to kit.

For Other Phone Models:

Flip the **Swivel Arm** up from 0° to 55° or 210° positions (or turn-on the unit).

Then press shortly the **Pick-Up/Hang-Up Button(7)**. The audio will be transferred from the phone to the kit.

REJECTING A CALL (Handsfree Profile only)

Press **Reject Button(2)** to reject an incoming call.

SETTING THE VOLUME

Set the volume using the **Volume Control(11)**.

1. Turn it clockwise to increase the volume.
2. Turn it counter clockwise to decrease.

Note: If the volume set is too high, it can cause feedback (whistling sound), echo, or background noise during calls on some cell phones.